

# 753 Series

## Miniature Partial Discharge Simulator

■ The Miniature Partial Discharge Simulator is a compact, battery operated discharge simulator. It injects a known PD signal into a PD test circuit to allow verification of calibration. It can be used to check any partial discharge detection installation where a PD detector has a measuring frequency less than 500 KHz.

A function switch selects a partial discharge level to be injected into the test circuit. The unit also incorporates a fine frequency control for synchronizing to a multiple of the mains frequency. An LED indicates the condition of the battery.

### Features

- Fine frequency control
- Three different pulse levels
- Common banana type connection
- LED indicator light
- Replaceable battery
- Light weight
- Durable

### Technical Specifications

#### General

Battery	9 V type pp3
Rise Time	300ns
Repetition Rate	1.2 kHz
Frequency Variation	+/- 50Hz min
Polarity	Alternating positive neg.

#### Weights and Dimensions (W x H x D, net weight, ship weight)

5 x 4 x 2 ¾ in, 1.1 lbs, 2 lbs
--------------------------------

### Applications

- ➔ Calibration for partial discharge measurements

### Ordering Information

#### Model

<b>753-US</b>	2, 5, 10 pC
<b>753-US1</b>	0.5, 5, 50 pC
<b>753-US2</b>	5, 50, 500 pC



Subject to technical modifications without notice.

European Contact  
Haefely Test AG  
Lehenmattstrasse 353  
CH-4028 Basel  
Switzerland  
☎ + 41 61 373 4111  
☎ + 41 61 373 4912  
✉ [sales@haefely.com](mailto:sales@haefely.com)

Locate your local  
sales representative at  
[www.high-voltage-hubbell.com](http://www.high-voltage-hubbell.com)



USA Contact  
Hipotronics Inc.  
1650 Route 22  
PO Box 414  
Brewster, NY 10509 USA  
☎ + 1 845 279 8091  
☎ + 1 845 279 2467  
✉ [sales@hipotronics.com](mailto:sales@hipotronics.com)